

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/01/2022

Reviewed on 07/01/2022

1 Identification

- **Product identifier**
- **Trade name:** *Peak™ Universal Bond*
- **Article number:** *SDS 206-001.13, 71057*
- **Application of the substance / the mixture** *Professional Dental Adhesive*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*Ultradent Products Inc.
505 W. Ultradent Drive (10200 S)
South Jordan, UT 84095-3942
USA
onlineordersupport@ultradent.com*
- **Information department:** *Customer Service*
- **Emergency telephone number:**
*During normal opening times: +1 (801) 553-4862
CHEMTREC (NORTH AMERICA) : (800) 424-9300
(INTERNATIONAL) : +(703) 527-3887*

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3 H226 Flammable liquid and vapor.



GHS05 Corrosion

Skin Corrosion 1A H314 Causes severe skin burns and eye damage.

Eye Damage 1 H318 Causes serious eye damage.



GHS07

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements** *Void*
- **Hazard pictograms** *GHS02, GHS05, GHS07*
- **Signal word** *Danger*
- **Health Hazard-determining components of labeling:**
*Methacrylic Acid
2-Hydroxyethyl Methacrylate
Trade Secret
Organophosphine Oxide*

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/01/2022

Reviewed on 07/01/2022

Trade name: Peak™ Universal Bond

(Contd. of page 1)

- **Hazard statements**

H226 Flammable liquid and vapor.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe dusts or mists.
 P264 Wash thoroughly after handling.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a poison center/doctor.
 P321 Specific treatment (see on this label).
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P363 Wash contaminated clothing before reuse.
 P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

64-17-5	Ethyl Alcohol	>10-≤25%
868-77-9	2-Hydroxyethyl Methacrylate	>10-≤25%
79-41-4	Methacrylic Acid	≥5-≤10%

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/01/2022

Reviewed on 07/01/2022

Trade name: Peak™ Universal Bond

(Contd. of page 2)

	Trade Secret	≥1-<5%
162881-26-7	Organophosphine Oxide	≥0.1-<1%

Additional information:

The specific chemical identity of composition is being withheld as a trade secret. The specific chemical identity is made available to health professionals, employees, and designated representatives in accordance with the applicable provisions of paragraph §1910.1200.

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Foam, dry chemical, carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:**
General: Evacuate all personnel; use protective equipment for fire fighting. Use self-contained breathing apparatus when the product is involved in fire.
Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/01/2022

Reviewed on 07/01/2022

Trade name: Peak™ Universal Bond

(Contd. of page 3)

See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Keep away from heat and direct sunlight.
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 See product labelling.
 Keep receptacle tightly sealed.
- **Specific end use(s)** Professional Dental Adhesive

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 At this time, the other constituents have no known exposure limits.

64-17-5 Ethyl Alcohol

PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
STEL	Short-term value: 1000 mg/m ³
TLV	Short-term value: 1000 ppm A3
TWA	Short-term value: 1900 mg/m ³

79-41-4 Methacrylic Acid

REL	Long-term value: 70 mg/m ³ , 20 ppm Skin
TLV	Long-term value: 20 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/01/2022

Reviewed on 07/01/2022

Trade name: Peak™ Universal Bond

(Contd. of page 4)

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material is based on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	Light yellow
Odor:	Acrylic
Odor threshold:	Not determined.

· **pH-value:** Not applicable (non-aqueous)

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	60 °C

· **Flash point:** 24 °C

· **Flammability (solid, gaseous):** Flammable.

· **Ignition temperature:** 425 °C

· **Decomposition temperature:** Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/01/2022

Reviewed on 07/01/2022

Trade name: Peak™ Universal Bond

(Contd. of page 5)

· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	3.5 Vol %
Upper:	15 Vol %
· Vapor pressure at 20 °C:	59 hPa
· Density at 20 °C:	1.1 g/cm ³
· Relative density	Not determined
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined
· Solvent content:	
VOC content:	38.80 %
	426.8 g/l / 3.56 lb/gal
VOC (EC)	<20.00 %
Solids content:	<15.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Oral	LD50	17,667 mg/kg
Dermal	LD50	8,333 mg/kg (rabbit)
Inhalative	LC50/4 h	118 mg/l

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/01/2022

Reviewed on 07/01/2022

Trade name: Peak™ Universal Bond

(Contd. of page 6)

64-17-5 Ethyl Alcohol

Oral	LD50	5,600 mg/kg (Guinea pig) 3,400 mg/kg (mouse) 7,060 mg/kg (rat)
	LC50 Fish	>10,000 mg/l (Fish)
Inhalative	LC50/4 h	39 mg/l (mouse) 20,000 mg/l (rat)

868-77-9 2-Hydroxyethyl Methacrylate

Oral	LD50	3,275 mg/kg (mouse) >5,000 mg/kg (rat)
	LC50 Fish	>100 mg/l (Fish)
Dermal	LD50	>3,000 mg/kg (rabbit)
	LC50(Daphnia magna)	24.1 mg/l (daphnia)

79-41-4 Methacrylic Acid

Oral	LD50	1,250 mg/kg (mouse) 1,060 mg/kg (rat) 1,200 mg/kg (rabbit)
	LC50 Fish	86 mg/l (Fish)
Dermal	LD50	1,000 mg/kg (Guinea pig) 500 mg/kg (rabbit)
	Inhalative LC50/4 h	7.1 mg/l (rat)

162881-26-7 Organophosphine Oxide

Oral	LD50	>2,000 mg/kg (rat)
	LC50 Fish	>0.09 mg/l (Fish) (Toxicity to fish)
Dermal	LD50	>2,000 mg/kg (rat)

· **Primary irritant effect:**· **on the skin:** Strong caustic effect on skin and mucous membranes.· **on the eye:**

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· **Sensitization:** Sensitization possible through skin contact.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

64-17-5	Ethyl Alcohol	1
128-37-0	Butylated Hydroxytoluene	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/01/2022

Reviewed on 07/01/2022

Trade name: Peak™ Universal Bond

(Contd. of page 7)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

64-17-5 Ethyl Alcohol

Algae Toxicity	1,000 mg/l (Algae)
----------------	--------------------

868-77-9 2-Hydroxyethyl Methacrylate

EC50	345 mg/kg (Algae)
------	-------------------

79-41-4 Methacrylic Acid

EC50	17,000 mg/kg (Algae)
	<180 mg/kg (daphnia) (Toxicity to aquatic invertebrates)

162881-26-7 Organophosphine Oxide

EC50 (static)	>1.175 mg/kg (daphnia) (Toxicity to aquatic invertebrates)
Aqua toxicity	≥0.008 mg/l (daphnia) (Daphnia Magna Reproduction Test)
Toxicity to Aquatic Plants (static)	>0.26 mg/l (Plant) (Toxicity to algae)

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Dispose of contents/container in accordance with international, federal, state, and local regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA**

UN2924

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/01/2022

Reviewed on 07/01/2022

Trade name: Peak™ Universal Bond

(Contd. of page 8)

· **UN proper shipping name**
 · **DOT**
 · **IMDG, IATA**

Flammable liquids, corrosive, n.o.s.
FLAMMABLE LIQUID, CORROSIVE, N.O.S. (METHACRYLIC ACID, STABILIZED, Ethyl Alcohol)

· **Transport hazard class(es)**· **DOT**

· **Class**
 · **Label**

3 Flammable liquids
3, 8

· **IMDG**

· **Class**
 · **Label**

3 Flammable liquids
3/8

· **IATA**

· **Class**
 · **Label**

3 Flammable liquids
3 (8)

· **Packing group**· **DOT, IMDG, IATA** *III*· **Environmental hazards:** *Not Applicable.*· **Special precautions for user** *Warning: Flammable liquids*· **Hazard identification number (Kemler code):** *38*· **EMS Number:** *F-E,S-C*· **Stowage Category** *A*· **Stowage Code** *SW2 Clear of living quarters.*

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** *Not Applicable.*

· **Transport/Additional information:**· **DOT**

· **Quantity limitations** *On passenger aircraft/rail: 5 L*
On cargo aircraft only: 60 L

· **IMDG**· **Limited quantities (LQ)** *5L*

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/01/2022

Reviewed on 07/01/2022

Trade name: Peak™ Universal Bond

(Contd. of page 9)

· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 2924 FLAMMABLE LIQUIDS, CORROSIVE, N.O.S. (METHACRYLIC ACID, STABILIZED, ETHYL ALCOHOL), 3 (8), III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

Trade Secret

· **Section 313 (Specific toxic chemical listings):**

1344-28-1 Aluminium Oxide

· **TSCA (Toxic Substances Control Act):**

64-17-5	Ethyl Alcohol	ACTIVE
868-77-9	2-Hydroxyethyl Methacrylate	ACTIVE
79-41-4	Methacrylic Acid	ACTIVE
	Trade Secret	ACTIVE
162881-26-7	Organophosphine Oxide	ACTIVE

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5 Ethyl Alcohol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **ACGIH Carcinogenicity (American Conference of Governmental Industrial Hygienists)**

64-17-5	Ethyl Alcohol	A3
1344-28-1	Aluminium Oxide	A4
128-37-0	Butylated Hydroxytoluene	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/01/2022

Reviewed on 07/01/2022

Trade name: Peak™ Universal Bond

(Contd. of page 10)

· **Chemical safety assessment:**

Device is biocompatible when used as directed by dental professionals per ISO 10993-1

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environmental, Health, and Safety

· **Contact:** Customer Service

· **Date of preparation / last revision** 07/01/2022 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Skin Corrosion 1A: Skin corrosion/irritation – Category 1A

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Sensitization - Skin 1: Skin sensitisation – Category 1

· *** Data compared to the previous version altered.**